

## EX612 – Multimedia Projector

### High Performance Data Projector

Captivate and engage your audience with Optoma's EX612, a versatile performer. Present bright, vibrant images even in ambient light conditions, making the EX612 your projector choice for nearly any classroom, large conference room or meeting room. The EX612 is equipped to deliver brilliant presentations with the latest color and image processing technologies from Texas Instruments. The Optoma EX612 is the perfect projector for providing a powerful image every time you turn it on!



### Features

- Brilliant large-screen display - 3500 ANSI lumens
- Easy-to-read text – 3000:1 contrast ratio
- Quick power-on and -off
- Filter-free design and long lamp life (up to 4000 hours) for low cost of ownership
- Upgrade with optional wireless dongle



### Specifications

**Display Technology**  
Single 0.55" DMD DLP®  
Technology by Texas Instruments

**Resolution**  
Native XGA (1024 x 768)

**Maximum Resolution**  
UXGA (1600 x 1200)

**Brightness (Typical)**  
3500 ANSI Lumens

**Contrast Ratio**  
3000:1 (Full On/Full Off)

**Lamp Life and Type**  
4000/3000 Hours (STD/Bright)  
230W P-VIP

**Throw Ratio**  
1.95 to 2.15:1 (Distance/Width)

**Projection Distance**  
3.93' to 39.3 (1.2 to 12m)

**Image Size (Diagonal)**  
27.5" to 303" (0.7 to 7.69m)

**Aspect Ratio**  
4:3 Native, 16:9 and 16:10  
Compatible

**Audio**  
2-Watt Speaker

**Offset**  
115%

**Displayable Colors**  
1.07 Billion

**Uniformity**  
85%

**Remote Control**  
IR Remote Control

**Computer Compatibility**  
UXGA, WXGA, SXGA+, SXGA, XGA,  
SVGA, VGA Resized, VESA, PC and  
Macintosh Compatible

**Video Compatibility**  
NTSC, PAL, SECAM, SDTV (480i),  
EDTV (480p), HDTV (720p, 1080i/p)

**Loop Through**  
Monitor: D-Sub 15-Pin VGA Output  
Audio: Mini-Jack Stereo Output  
(Functional in Both Normal and  
Standby Modes)

**Projection Lens**  
F=2.4-2.55, f=21.8-24mm, 1.1x  
Manual Zoom and Focus

**User Controls**  
Complete On-Screen Menu  
Adjustments in 23 Languages

**I/O Connectors**  
Two VGA-In, VGA-Out, S-Video,  
Composite Video, Stereo Audio-In,  
Stereo Audio-Out, RS-232 and USB

**Security**  
Kensington® Lock, Security Bar and  
Keypad Lock

**Projection Method**  
Front, Rear, Ceiling Mount, Table  
Top

**Weight**  
6.4 lbs (2.9kg)

**Dimensions (W x H x D)**  
12.76" x 3.82" x 9.21"  
(324 x 97 x 234 mm)

**Noise Level (STD/Bright)**  
29dB/31dB

**Keystone Correction**  
±40° Vertical

**Horizontal Scan Rate**  
15.3 to 91.1 KHz

**Vertical Refresh Rate**  
25 to 85 Hz

**Operating Temperature**  
41 to 104°F (5 to 40°C), 80% Max  
Humidity

**Power Supply**  
AC Input 100-240V, 50-60Hz,  
Auto-Switching

**Power Consumption**  
328 Watts (Bright), 272 Watts (STD),  
<1 Watt (Standby)

**Standard Accessories**  
AC Power Cord, VGA to VGA Cable,  
Remote Control, Batteries for Remote,  
Carrying Case, Lens Cap, CD-ROM  
User's Manual, Quick Start Card and  
Warranty Card

**Optional Accessories**  
Ceiling Mount, Wireless Dongle, VGA  
to Component Cable, S-Video Cable,  
Composite Video Cable, RS-232 Cable  
and Panoview™ Series Screens

**Warranty**  
One Year Limited Parts and Labor,  
90 Days on Lamp

**UPC**  
796435 41 129 9

**Accessory Part Numbers**  
Lamp: BL-FP230D  
Remote: BR-3044N  
Mount: BM-5001U  
Case: BK-4028  
Wireless Dongle: BI-EXTGB