

Mitsubishi Optional Lens Specifications

XL7100, WL7200, UL7400 OL-XL7100SZ	
Type	Short Throw Zoom Lens
Zoom Ratio	1.3:1
Focal Length	19.3 - 24.9 mm
F Number	F2.0-2.6
Focus/Zoom	Motorized Focus & Zoom
Throw Ratio	XL7100 1.2 - 1.5 (2.4 - 3.1 m@100") cf. Standard Lens 1.5 - 2.7 (3.0 - 5.4 m@100") WL7200 1.2 - 1.5 (2.5 - 3.3 m@100") UL7400 1.2 - 1.5 (2.5 - 3.2 m@100")
Off set axis	XL7100 V Shift(Height) +/-60% , H Shift(Width) +/-30% (same as standard lens) WL7200 V Shift(Height) +/-70% , H Shift(Width) +/-30% (same as standard lens) UL7400 V Shift(Height) +60%/-20% , H Shift(Width) +/-30% (same as standard lens) (T.B.D) (Maximum values for vertical/horizontal lens shift cannot be set simultaneously)

XL7100, WL7200, UL7400 OL-XL7100LZ	
Type	Long Throw Zoom Lens
Zoom Ratio	1.7:1
Focal Length	42.3 - 71.8 mm cf. Standard Lens 24.0 - 43.2mm
F Number	F 2.2 - 2.8
Focus/Zoom	Motorized Focus & Zoom
Throw Ratio	XL7100 2.6 - 4.4 (5.3 - 9.0 m@100") cf. Standard Lens 1.5 - 2.7 (3.0 - 5.4 m@100") WL7200 2.6 - 4.4 (5.5 - 9.5 m@100") UL7400 2.5 - 4.4 (5.5 - 9.4 m@100")
Off set axis	XL7100 V Shift(Height) +/-60% , H Shift(Width) +/-30% (same as standard lens) WL7200 V Shift(Height) +/-70% , H Shift(Width) +/-30% (same as standard lens) UL7400 V Shift(Height) +60%/-20% , H Shift(Width) +/-30% (same as standard lens) (T.B.D) (Maximum values for vertical/horizontal lens shift cannot be set simultaneously)

XL7100, WL7200, UL7400 OL-XL7100TZ	
Type	Tele Throw Zoom Lens
Zoom Ratio	1.7:1
Focal Length	70.3 - 119.5 mm cf. Standard Lens 24.0 - 43.2mm
F Number	F 2.2 - 2.8
Focus/Zoom	Motorized Focus & Zoom
Throw Ratio	XL7100 4.3 - 7.4 (8.7 - 15.0 m@100") cf. Standard Lens 1.5 - 2.7 (3.0 - 5.4 m@100") WL7200 4.3 - 7.3 (9.2 - 15.8 m@100") UL7400 4.2 - 7.2 (9.1 - 15.6 m@100")
Off set axis	XL7100 V Shift(Height) +/-60% , H Shift(Width) +/-30% (same as standard lens) WL7200 V Shift(Height) +/-70% , H Shift(Width) +/-30% (same as standard lens) UL7400 V Shift(Height) +60%/-20% , H Shift(Width) +/-30% (same as standard lens) (T.B.D) (Maximum values for vertical/horizontal lens shift cannot be set simultaneously)

XL7100, WL7200, UL7400 OL-XL7100FR	
Type	Fixed Focal Rear Lens
Zoom Ratio	Fixed zoom
Focal Length	12.9 mm cf. Standard Lens 24.0 - 43.2mm
F Number	F 2.2
Focus	Motorized Focus
Throw Ratio	XL7100 0.8 (1.6 m@100") cf. Standard Lens 1.5 - 2.7 (3.0 - 5.4 m@100") WL7200 0.8 (1.7 m@100") UL7400 0.8 (1.7 m@100")
Off set axis	1 : 1 (No variable lens shift)



PRESENTATION PRODUCTS

Mitsubishi Electric Visual Solutions America
Presentation Products Division
9351 Jeronimo Road
Irvine, CA92618
Toll Free: 888-307-0349
email: pppinfo@mdea.com